# PRODUCT RANGE 2022

Husqvarna

## PETROL POWER CUTTERS

**HUSQVARNA K 1270**
119 cc. 5.8 kW. 13.3/13.7 kg. blade size 350/400 mm. cutting depth 118/145 mm.

NEW **HUSQVARNA K 1270 SMARTGUARD**
119 cc. 5.8 kW. 15.1 kg blade size 400 mm. cutting depth 118/145 mm.

**HUSQVARNA K 770 / K 770 WITH OILGUARD**
74 cc. 3.7 kW. 10 / 10.1 kg. blade size 300/350 mm. cutting depth 100/125 mm.

NEW **HUSQVARNA K 770 SMARTGUARD**
74 cc. 3.7 kW. 10.8 / 11.1 kg. blade size 300/350 mm. cutting depth 100/125 mm.

**HUSQVARNA K 970**
94 cc. 4.8 kW. 11/11.6 kg. blade size 350/400 mm. cutting depth 125/155 mm.

NEW **HUSQVARNA K 970 SMARTGUARD**
94 cc. 4.8 kW. 11.9/12.8 kg. blade size 350 /400 mm. cutting depth 125 /155 mm.

**HUSQVARNA K 770 VAC**
74 cc. 3.7 kW. 11.0 kg. blade size 305 mm. cutting depth 123 mm.

**HUSQVARNA K 770 DRY CUT**
74 cc. 3.7 kW. 12.0 kg. blade size 305 mm. cutting depth 123 mm.

**HUSQVARNA K 970 RING**
94 cc. 4.8 kW. 13.8 kg. blade size 370 mm. cutting depth 270 mm.

**HUSQVARNA K 760 CUT-N-BREAK**
74 cc. 3.7 kW. 11.1 kg. blade size 230 mm. cutting depth 400 mm.

**HUSQVARNA K 970 CHAIN**
94 cc. 4.8 kW. 9.7 kg. bar size 350 mm. cutting depth 400 mm.

## RESCUE CUTTERS

**HUSQVARNA K 970 RESCUE**
94 cc. 4.8 kW. 11 kg. blade size 350 mm. cutting depth 125 mm.

**HUSQVARNA K 770 RESCUE**
74 cc. 3.7 kW. 9.6 kg. blade size 300 mm. cutting depth 100 mm.

## RAIL CUTTER

**HUSQVARNA K 1270 RAIL**
119 cc. 5.8 kW. 20.5/21.2 kg (incl RAIL). blade size 350 /400 mm. cutting depth 118 / 145 mm.

## HYDRAULIC POWER CUTTERS

**HUSQVARNA K 3600 MK II**
150 bar/40 l min. 4.3 kW. 8.3 kg. blade size 370 mm. cutting depth 270 mm.

**HUSQVARNA K 2500**
150 bar/40 l/min. 5.2 kW. 8.3 kg. blade size 400 mm. cutting depth 145 mm.

## ELECTRIC POWER CUTTERS

PRIME **HUSQVARNA K 7000**
230/400 V. 5.5 kW (3-phase) / 3 kW (1-phase). 9.8 kg. blade size 400 mm. cutting depth 155 mm.

NEW **HUSQVARNA K 7000 SMARTGUARD**
230 /400 V. 5.8 kW (3-phase)/ 3 kW (1-phase). 5.1 kg. blade size 400 mm. cutting depth 145 mm.

PRIME **HUSQVARNA K 7000 RING**
230/400 V. 5.5 kW (3-phase)/ 3 kW (1-phase). 13.1/12.4 kg. blade size 350/425 mm. cutting depth 270/325 mm.

**HUSQVARNA K 7000 CHAIN**
230/400 V. 5.5 kW (3-phase)/3 kW (1-phase). 9.1 kg. bar size 450 mm. cutting depth 450 mm.

**HUSQVARNA K 4000**
230/120/110 V. 2700/1800/2200 W. 8.5 kg (incl. Vac attachment 1 kg). blade size 350 mm. max. cutting depth 125 mm.

**HUSQVARNA K 4000 CUT-N-BREAK**
230/120/110 V. 2700/1800/2200 W. 8.9 kg. blade size 230 mm. cutting depth 400 mm.

## AIR POWER CUTTER

**HUSQVARNA K 40**
7 kp/cm². 3.2 kW. 9.9 kg. blade size 350 mm. cutting depth 125 mm.

## CUTTING TROLLEYS

**HUSQVARNA KV 9/12**
Cutting trolley designed for K 970 and K 1270. Water tank 13.3 l.

**HUSQVARNA KV 7**
Cutting trolley designed for K 760 and K 770. Water tank 13.3 l.

## POWER CUTTERS – ACCESSORIES

**K 3000/K 4000 VAC ATTACHMENT**
Ideal dust collection enables you to cut without water. Fits K 3000 Wet/Vac and K 4000.

**HUSQVARNA RA 10**
Cutting attachment for the K 1260 Rail. 5.3 kg

**PIPE CLAMP KIT**
For use with Husqvarna K 970 Ring and Chain and K 6500 Ring and Chain. A convenient accessory for producing straight, precise cuts in concrete and iron pipes.

**PRESSURIZED WATER TANK PLUS HOSE**
Holds 13.3 litres, complete with a 3-metre hose.

## FLOOR SAWS

**HUSQVARNA FS 7000 DL**
Diamond blade max 1500 mm. 1338 kg. cutting depth 625 mm. 55.4 kW.*

**HUSQVARNA FS 7000 D**
Diamond blade max 1000 mm. 1032 kg. cutting depth 411 mm. 55.4 kW.*

**HUSQVARNA FS 5000 D**
Diamond blade max 900 mm. 771 kg. cutting depth 374 mm. 35.5 kW.*

**HUSQVARNA FS 4800 D**
Diamond blade max 900 mm. 680–695 kg. cutting depth 381 mm. 35 kW.*

**HUSQVARNA FS 3500 G**
Diamond blade max 750 mm. 419 kg cutting depth 311 mm. 27.5 kW.*

NEW **HUSQVARNA FS 600 E**
Diamond blade max 600 mm. cutting depth 240 mm. 178 kg. 7.5 kW.*

**HUSQVARNA FS 500 SERIES**
Diamond blade max 600/500 mm. cutting depth 241/179/192 mm. 231/197/145 kg. FS 524 petrol. 15.5 kW.*. FS 513 petrol. 8.7 kW.*. FS 500 E. electric. 7.5 kW.*.

**HUSQVARNA FS 400 SERIES**
Diamond blade max 500 mm. cutting depth 189 mm. 163 kg. FS 413 petrol. 8.7 kW.*. FS 410 D. diesel. 6.6 kW.*.

**HUSQVARNA FS 400 LV**
Diamond blade max 450 / 500 mm. cutting depth 162 / 189 mm. 99 kg. 8.7 kW.*.

**HUSQVARNA FS 300 SERIES**
Diamond blade max 350 mm. cutting depth 122/125 mm. 64/54 kg. FS 309. petrol. 6.6 kW.*. FS 305. petrol. 3.6 kW.*.

## DRILL MOTORS

PRIME **HUSQVARNA DM 700**
6000/3000 W. 3-phase/1-phase. electric. recommended drill diameter 80–600 mm. 14 kg.

**HUSQVARNA DM 400/DM 430**
3200 W. 1-phase. electric recommended drill diameter 55–450 mm. 14/15.5 kg.

**HUSQVARNA DM 220**
1850 W. 1-phase. electric. recommended drill diameter 150 mm. handheld 80 mm. 7.5 kg.

**HUSQVARNA DM 280**
2700 W. 1-phase. electric. recommended drill diameter. low speed 50–350 mm. high speed 25–250 mm. 13 kg.

**HUSQVARNA DM 406 H**
120/230/340/580/980/1400 rpm. recommended drill diameter 0–650 mm. 16 kg.

**HUSQVARNA DM 230**
1850 W. 1-phase. electric. recommended drill diameter 150 mm. handheld 80 mm. 7 kg.

**HUSQVARNA DM 200**
2000 W. 1-phase. electric. recommended drill diameter 25–100 mm. 6.4kg.

## DRILL STANDS

**HUSQVARNA DS 900**
Ø 900 mm. travel length 950 mm. 24 kg.

**HUSQVARNA DS 500**
Ø 500 mm. length 706 mm. 18 kg.

**HUSQVARNA DS 250/ DS 250 SINGLE SPEED**
Ø 250 mm. travel length 685 mm. 16 kg.

**HUSQVARNA DS 150**
Ø 150 mm. travel length 495 mm. 15.5 kg.

**HUSQVARNA DS 50 COMBI**
Ø 300 mm. travel length 1090 mm. 21 kg.

**HUSQVARNA DS 50 GYRO**
Ø 350 mm. travel length 670 mm. 56 kg.

**HUSQVARNA DS 40 GYRO**
Ø 150 mm. travel length 600 mm. 30 kg.

## ULTRA EARLY ENTRY™ SAWS

**HUSQVARNA SOFF-CUT 4200**
Diamond blade max 350 mm. cutting depth max 76 mm. 257 kg. 17.2 kW.*

**HUSQVARNA SOFF-CUT 150**
Diamond blade max 150 mm. cutting depth max 30 mm. 40 kg. 4.0 kW.*

**HUSQVARNA SOFF-CUT 4000**
Diamond blade max 350 mm. cutting depth max 70 mm. 191 kg. 14.9 kW.*

**HUSQVARNA SOFF-CUT 2000**
Diamond blade max 250 mm. cutting depth max 38 mm. 144 kg. 6.5 kW.*

NEW **HUSQVARNA DE 110**
1.1 kW. 220–240 V. 5 A. 240 m³/h. 25 kg

NEW **HUSQVARNA DE 120**
2.2 kW. 220–240 V. 15 A. 480 m³/h. 39 kg

**HUSQVARNA C 3000**
63 mm. 37 l. 22 kg.

**HUSQVARNA C 5500**
76 mm. 100 l. 67 kg

NEW **HUSQVARNA DE 110 S**
0.9 kW. 220–240 V 4 A. 215 m³/h. 25 kg

**HUSQVARNA W 70**
1.2 kW. 220–230 V. 5 A. 200 m³/h. 34 kg

**HUSQVARNA W 70 P**
1.2 kW. 220–230 V. 8 A. 200 m³/h. 44 kg

**HUSQVARNA W 250 P**
1.2 kW. 220–230 V. 7 A. 160 m³/h. 27 kg.

**HUSQVARNA S 36**
36 kW. 220–230 V. 14 A. 600 m³/h. 65 kg.

**HUSQVARNA A 2000**
0.75 kW. 220–230 V. 3.3 A. 36 kg

**HUSQVARNA A 1000**
0.285 kW. 220–230 V. 1.2 A. 18 kg.

## DRILL MOTORS WITH STANDS

**HUSQVARNA DMS 240**
2400 W. 1 phase. electric. max Ø 250 mm. 20.4 kg.

**HUSQVARNA DMS 160 AT/A**
1550 W. 1 phase. electric. max Ø 120 mm. 12/105 kg.

## TILE SAWS

**HUSQVARNA TS 60**
1800 W. max Ø 254 mm. max cutting depth 78/45 mm. 36 kg.

**HUSQVARNA TS 73 R**
1000 W. max Ø 230 mm. max cutting depth 50/100 mm. 47 kg.

**HUSQVARNA TS 66 R**
800 W. max Ø 200 mm. max cutting depth 40 mm. 41 kg.

## MASONRY SAWS

**HUSQVARNA TS 400 F**
1500/2200 W. max Ø 400 mm. max cutting depth 125/230 mm. 96 kg.

**HUSQVARNA TS 300 E**
2200 W. max Ø 300 (350) mm. max cutting depth 80 (100) mm. 82 kg

**HUSQVARNA TS 350 E**
1500/2200 W. max Ø 350 mm. max cutting depth 100 mm. 92 kg

**HUSQVARNA TS 100 R**
2200 W. max Ø 350 mm. max cutting depth 105 mm. 106 kg

## DUST AND SLURRY MANAGEMENT

**HUSQVARNA T 10000**
11 kW. 380 – 415 V. 32 A. 900 m³/h. 336 kg

**HUSQVARNA HTC D80**
7.5 kW. 230–400 V. 16.7 A. 700 m³/h. 272 kg

**HUSQVARNA HTC D60**
5.5 kW. 230–480 V. 15 A. 530 m³/h. 179 kg

**HUSQVARNA T 7500**
5.5 kW. 380 – 415 V. 16 A. 600 m³/h. 206 kg

## EQUIPMENT FOR SURFACE PREPARATION

## COMPACTION EQUIPMENT

## TAMPERS

**HUSQVARNA LT 8005**
3 kW. 98–99 kg

**HUSQVARNA LT 6005**
2.7 kW. 69 – 70 kg

**HUSQVARNA LT 5005**
2.7 kW. 61 – 62 kg

## FORWARD PLATE COMPACTORS ASPHALT AND SOIL

**HUSQVARNA LF 100 LAT**
2.5–3.6 kW. 500 mm. 109 – 118 kg

**HUSQVARNA LF 80 LAT**
3.6 kW. 420 mm. 95 kg

**HUSQVARNA LF 75 LAT**
3.6 kW. 420–500 mm. 95–97 kg

**HUSQVARNA LF 60 LAT**
2.3 kW. 350 mm. 67 kg

## FORWARD PLATE COMPACTORS – SOIL

**HUSQVARNA LF 130 LT**
2.5–3.6 kW. 500 mm. 135 – 142 kg

**HUSQVARNA LF 80 L**
3.6 kW. 420 mm. 84 kg

**HUSQVARNA LF 50 L**
2.3 kW. 320 mm. 53 kg

## FORWARD AND REVERSIBLE PLATE COMPACTORS

**HUSQVARNA LH 804**
11 kW. 820 kg

**HUSQVARNA LG 504**
9.2 kW. 470–513 kg.

**HUSQVARNA LG 400**
6.2–8.3 kW. 398–436 kg

**HUSQVARNA LG 300**
4.7–5.3 kW. 265–307 kg.

**HUSQVARNA LH 700**
11 kW. 780 kg.

**HUSQVARNA LG 204**
3.1–4.1 kW. 211–251 kg

**HUSQVARNA LG 164**
3.1–3.6 kW. 148–185 kg.

## ROUND PLATE COMPACTOR

NEW **HUSQVARNA LX 95**
3.6 kW. 430 mm. 100kg

**HUSQVARNA LX 90**
3.6 kW. 450 mm. 96 kg

## DOUBLE DRUM ROLLERS

**HUSQVARNA LP 9505**
17.8 kW. drum width 850 mm. 1675 kg.

**HUSQVARNA LP 7505**
7.9 kW. drum width 750 mm. 981–1001 kg.

**HUSQVARNA LP 6505**
7.2 kW. drum width 650 mm. 745–765 kg.

## PNEUMATIC VIBRATORS

**HUSQVARNA AY SERIES**
9 diameters. 26–155 mm. hose length 2 or 4 m. 4–28 kg.

## EXTERNAL VIBRATORS

**HUSQVARNA PNEUMATIC AND ELECTRIC VIBRATORS**
14 versions. Speed 3000 – 9350 rpm. max. centrifugal force 500 – 31500 N.

## WALK-BEHIND SCREEDS

**HUSQVARNA BV 30**
1 kW. centrifugal clutch. petrol. 14 kg.

**HUSQVARNA BV 20 H**
2.0 m. 7.5 kg.

**HUSQVARNA BV 20 G**
2.0 × 2.2–4 m (8× L) 0.7 kW. petrol. 16.6 kg.

## DOUBLE BEAM SCREEDS

**HUSQVARNA BE 30**
2.6 kW. 32 kg.

**HUSQVARNA BE 20**
0.45 kW. 37 kg.

**HUSQVARNA BD 32/42/52/62**
3.2. 4.2. 5.2. 6.2 m. 32–57 kg

## SCREED BLADES

**HUSQVARNA BV 30 SCREED BLADE**
1.8/2.4/3.0/3.6/4.2 m

## SCREED SECTIONS

**HUSQVARNA BT 90**
0.5/0.75/1/2/3 m.

## MODULAR SCREEDS

**HUSQVARNA BT 90 E**
3 kW. 20 m. 96 kg

**HUSQVARNA BT 90 G**
5 kW. 20 m. 93 kg.

**HUSQVARNA BT 90 P**
25 m. 40 kg.

## WALK BEHIND TROWELS

**HUSQVARNA CT 48**
5.9–8.7 kW. 1180 mm. 105–125kg

**HUSQVARNA CT 36**
3.6–5.9 kW. 875 mm. 85–94kg

**HUSQVARNA BG 475**
6.3 kW. 1140 mm. 105 kg

**HUSQVARNA BG 375**
3.6 – 6.3 kW. 900 mm. 88 –102 kg.

**HUSQVARNA BG 245 H**
2.5 kW. 600 mm. 58 kg.

## ELECTRIC WALK BEHIND TROWELS

**HUSQVARNA BG 245 E**
1.5 kW. 600 mm. 60 kg.

**HUSQVARNA BG COMBI**
1.8 – 2.4 kW. 1020 – 850 mm. 88 – 86 kg.

## TROWEL BLADES AND FLOATING DISCS

HUSQVARNA PROLINE

HUSQVARNA CLASSIC LINE

## HUSQVARNA FLOOR GRINDERS

**HUSQVARNA PG 830 RC**
16.5 kW. 380/415 V. 3-phase. grinding width 800 mm. grinding disc 3 × 270 mm. 598 kg.

**HUSQVARNA PG 830**
16.5 kW. 380/415 V. 3-phase. grinding width 800 mm. grinding disc 3 × 270. 556 kg.

**HUSQVARNA PG 690 RC**
12.5 kW. 380/415 V. 3-phase. grinding width 640 mm. grinding disc 3 × 270. 598 kg.

**HUSQVARNA PG 690**
12.5 kW. 380/415 V. 3-phase. grinding width 640 mm. grinding disc 3 × 270. 502 kg.

**HUSQVARNA PG 830 S**
11 kW. 380/415 V. 3-phase. grinding width 800 mm. grinding disc 3 × 270. 497 kg.

**HUSQVARNA HTC 8**
12/15 kW. 380/415 V. 3-phase. grinding width 800 mm. grinding disc 3 × 270/4 × 270. 499/574 kg.

**HUSQVARNA HTC 6**
7.5 kW. 380/415 V. 3-phase. grinding width 600 mm. grinding disc 3 × 230/4 × 230 mm. 384/441 kg.

**HUSQVARNA HTC 5**
4.0/2.2 kW. 400/220 V. 3-phase/1-phase. grinding width 515 mm. grinding disc 3 × 230. 122/179 kg.

**HUSQVARNA PG 540**
4.0/2.2 kW. 400/220 V. 3-phase/1-phase. grinding width 515 mm. grinding disc 3 × 230 mm. 178/169 kg.

**HUSQVARNA PG 510**
4.0/2.2 kW. 400/220 V. 3-phase/1-phase. grinding width 515 mm. grinding disc 3 × 230 mm. 133/120 kg.

**HUSQVARNA PG 450**
2.2 kW. 230 V. 1-phase. grinding width 450 mm. grinding disc 3 × 180 mm. 109 kg.

**HUSQVARNA PG 400**
4 kW. 400 V. 3-phase. grinding width 400 mm. 115 kg

**HUSQVARNA PG 280**
3/2.2 kW. 400/220 V. 3-phase/1-phase. grinding width 280 mm. 70 kg.

**HUSQVARNA CG 200**
2.2 kW. 220–240 V. 1-phase. grinding width 200 mm. 58 kg.

**HUSQVARNA CG 200**
3.6 kW. petrol. grinding width 200 mm. 54 kg.

## TOOLS FOR SURFACE PREPARATION

### REDI TOOL SYSTEM

**HUSQVARNA ELITE-GRIND G 1400 SERIES**
Segments designed to offer optimal performance in all types of applications. Five different bonds. Grit range from 20 to 100.

**HUSQVARNA SHARX™**
For fast and easy removal of dense surfaces on hard-troweled concrete floors.The metal bond ensures that the pads stay opened and sharp even on the hardest top layers.

**HUSQVARNA PIRANHA™**
PCD tooling designed for fast and aggressive removal of many hard-to-remove coatings and screeds.

**HUSQVARNA VARI-GRIND G 600 SERIES**
Silver level segments in an optimized range to facilitate tool selection. Three different bonds. Grit range from 20 to 100.

**HUSQVARNA BUSH HAMMERING TOOLS**
This series is developed for creating a bush hammered surface or to expose large aggregate. but also for creating a bush hammered profile perfect for high traction exterior surfaces.

**HUSQVARNA EDGE GRINDING**
Metal cup wheels and flexible pads for handheld grinding.

**HUSQVARNA HIPERFLEX SERIES**
Resin-bonded polishing tool on a flexible pad. Can be used both dry and wet for overlayments and high quality polished concrete

**HUSQVARNA CP 1200 SERIES**
Ceramic tools with velcro backing for dry grinding and polishing of concrete. Grit range from 30 to 400.

**HUSQVARNA P 1200 SERIES**
Resin bond polishing pads can be chosen for high-end polishing. Grit range from 50 to 3000.

**HUSQVARNA HIPERTROWEL™ FLOOR POLISHING SYSTEM**
Polish large concrete floors fast with a ride-on power trowel and Hiperflex TRW tool pads mounted on flexible Hipertrowel™ gyro drivers.

**HUSQVARNA HIPERCLEAN PADS**
Diamond impregnated maintenance pads, ideal for cleaning concrete polished floors.

**HUSQVARNA SCARIFYING TOOLS**
A gold level range of scarifying drums with different steel and carbide wheels that cover applications from coating removal to grooving.

### EZ TOOL SYSTEM (HTC)

REMOVAL AND PREPARATION

**EZ PREP SERIES**
The EZ PREP series is designed for efficient removal and is available in four variants, depending on floor hardness.

**T-REX SERIES**
The T-REX series with PCDs is designed for aggressive removal and is available with EZ change attachment and as rings.

**RAVAGER SERIES**
This series is developed for creating a bush-hammered surface or to expose large aggregates.

METAL TOOLS TOOLS

**THE SMHXX SERIES FOR CONCRETE GRINDING**
The SMHXX series consists of five different tool series, covering all surfaces from soft/abrasive to extremely hard when nothing else works.

**TOOL RINGS**
The tool rings are suitable for our smaller grinders since fewer segments per tool means more weight and power into the floor.

RESIN TOOLS

**SF SERIES**
Our premium resin technology combined with optimised flexible design.

**EZ SP SERIES**
This high-performing concrete polishing tools series performs on all types of concrete

### TOOL HOLDER MULTI

A tool holder allowing to attach both Redilock and EZ change tools to your Husqvarna grinders. For ultimate versatility.

**SPECIAL APPLICATIONS**
Diamond Fenix and Diamond block series are designed for cementitious toppings resp. applications requiring high temperature resistant resin.

**EDGE GRINDING SERIES**
This portfolio offers corresponding tools for what you can find for our planitary grinders. Everything from extreme removal to high gloss polishing.

**WOOD GRINDING SERIES**
The wood series is a single layer diamond tool specifically developed for efficient initial grinding of wood. Oiling pads are also available for post treatment.

**NATURAL STONE SERIES**
SGR and Diamond Xpress cover our natural stone portfolio specifically developed for wet resp. dry processing.

## WALL SAWS

**HUSQVARNA WS 482 HF**
High frequency. wireless remote control. diamond blade 600–1600 mm. 28 kg. cutting depth 730 mm.

**HUSQVARNA WS 440 HF**
High frequency. wireless remote control. diamond blade 600–1200 mm. 25 kg. cutting depth 530 mm.

**HUSQVARNA WS 220**
High frequency. wireless remote control. diamond blade 500–900 mm. 19 kg. cutting depth 395 mm.

PRIME **HUSQVARNA WSC 40**
Attachment that converts your Husqvarna WS 482 HF and WS 440 HF from blade to chain sawing. Max cutting depth. 400 mm. 19 kg.

## REMOTE DEMOLITION

NEW **HUSQVARNA DXR 315**
27 kW. 2020 kg. reach 5.5/5.2 m up/forward incl. tool.

NEW **HUSQVARNA DXR 305**
27 kW. 1960 kg. reach 5.5/5.1 m up/forward incl. tool.

NEW **HUSQVARNA DXR 275**
24 kW. 1750 kg. reach 4.8/4.5 m up/forward incl. tool.

NEW **HUSQVARNA DXR 145**
18.5 kW. 985 kg. reach 4.4/3.7 m up/forward incl. tool.

## WIRE SAWS

**HUSQVARNA CS 2512**
Wire speed 20 or 25 m/s. magazine capacity 12 m (ready to use 15 m). 150 kg.

**HUSQVARNA CS 10**
Wire speed 24 m/s. magazine capacity 10 m. 138/135 kg.

## POWER PACKS

**HUSQVARNA PP 492**
20 kW. 25 kg.

PRIME **HUSQVARNA PP 220**
6.5 kW. 10 kg.

PRIME **HUSQVARNA PP 70**
3-phase/1-phase 6.5 kW. 18 kg

**HUSQVARNA PP 455 E**
65 l/min. 230 bar. 25 kW. 139 kg.

**HUSQVARNA PP 325 E**
40 l/min. 140 bar. 9.3 kW. 95 kg

**HUSQVARNA PP 518**
20. 30. 40 l/min. 140 bar. 10.4 kW. 145 kg.

## REMOTE DEMOLITION – TOOLS

**HUSQVARNA DCR 300 AND DCR 100**
For Husqvarnas demolition robots. With these powerful crushers you can easily crush a 400 mm thick concrete wall. staircases. pillars etc.

**HUSQVARNA DSS 200**
For Husqvarnas demolition robots. Steel shearer for demolition of structures. piping. process vessels and tanks. Ideal in sensitive areas such as process industries.

**HUSQVARNA BUCKETS**
Available in three sizes. For DXR 140: Standard 52 cm/ 55 liters. Wide 77 cm/60 liters. Narrow 30 cm/ 40 liters. All other DXRs: Standard 52 cm/85 liters. Wide 77 cm/105 liters. Narrow 30 cm/40 liters.

## PACE PACE BATTERY SYSTEM

## BATTERY POWER CUTTER

NEW **HUSQVARNA K 1 PACE**
7.2/7.4 kg. blade size 300/350 mm. cutting depth 121/144.5 mm.

NEW **HUSQVARNA K 1 PACE RESCUE**
7.9 kg. blade size 350 mm. cutting depth 144.5 mm.

## DIAMOND BLADES FOR PACE BATTERY POWER CUTTER

NEW C **HUSQVARNA ELITE-CUT S 35 S BAT**
Providing a maximum cutting speed and wear resistance in all heavy cutting job. Low vibrations with the continuous rim and silence core.

S **HUSQVARNA VARI-CUT FR3**
Has one layer of vacuum brazed diamond for fast cutting of a large variety of materials like tiles. stone. rebars. fiber board. PVC pipes and more. Possible to use in standard PC.

NEW S **HUSQVARNA TACTI-CUT S 35 S BAT**
Providing a good balance between performance and price in all cutting operation. Low vibrations with the continuous rim and silence core.

B **HUSQVARNA ABRASIVE DISCS**
Conventional abrasive disc specially recommended to cut metal and rebars possible to use in standard PC.

## ACCESSORIES

NEW **HUSQVARNA BB380X/B750X PACE**
High power PACE batteries equipped with built-in connectivity. Capacity: 375/750 Wh. weight 3/5 kg.

NEW **HUSQVARNA C900X/C1800X**
High power battery chargers with a fast charging mode and active cooling. Capacity of 1800 W.

NEW **VAC ATTACHMENT**
Ideal dust collection enables you to cut without water.

## I-SERIES BATTERY SYSTEM

### BATTERY POWER CUTTER

**HUSQVARNA K 535i**
3.5 kg. blade size 230 mm. cutting depth 76 mm. i-Series battery system.

### BATTERY SCREED

**HUSQVARNA BV 30i**
The battery-powered BV 30i screed is the eco-sensible choice paired with improved ergonomics. easy operation and low maintenance.

### DIAMOND BLADES FOR I-SERIES BATTERY POWER CUTTER

C **HUSQVARNA ELITE-CUT S 35 S BAT**
Providing a maximum cutting speed and wear resistance in all heavy cutting job. Low vibrations with the continuous rim and silence core.

S **HUSQVARNA VARI-CUT FR3**
Has one layer of vacuum brazed diamond for fast cutting of a large variety of materials like tiles. stone. rebars. fiber board. PVC pipes and more. Possible to use in standard PC.

S **HUSQVARNA TACTI-CUT S 35 S BAT**
Providing a good balance between performance and price in all cutting operation. Low vibrations with the continuous rim and silence core.

B **HUSQVARNA ABRASIVE DISCS**
Conventional abrasive disc specially recommended to cut metal and rebars possible to use in standard PC.

### BATTERY DRILL MOTORS

NEW **HUSQVARNA DM 540i**
1.850 W. recommended drill diameter 0.15–75 mm (100 mm with a drill stand). 4.9 kg. i-Series battery system.

NEW **HUSQVARNA WT 15i**
220/110 V electric pump. Holds 15 litres. Battery-powered. 36 V.

### BATTERY DUST EXTRACTOR

NEW **HUSQVARNA DE 110i**
DE 110i is a versatile and compact H-class dust extractor powered by Husqvarna BLi 36 V batteries.

NEW **HUSQVARNA WL 8i**
Extremely durable and powerful battery powered lighting solution – up to 8000 lumen. Easy to carry and position. easy to change from flood light to 360 degree area light using the light diffuser accessory. Built-in power bank with USB outlet to charge mobile devices. Using the tripod accessory gives an adjustable height between 1.35 and 3 m.

### ACCESSORIES

**HUSQVARNA QC330/QC500**
Quick charging unit with 2-LED status indicator and active battery cooling for minimum charge time and longer battery life.

**HUSQVARNA BLi 100/200/300**
All-weather operation and excellent cooling. Rechargeable more than 1,500 times. 2.6/5.2/9.4 Ah. 0.8/1.3/1.9 kg

**VAC ATTACHMENT**
Ideal dust collection enables you to cut without water.

## HUSQVARNA DIAMOND TOOLS COME IN THREE PERFORMANCE CATEGORIES:

**GOLD**
Husqvarna diamond tools at Gold level are developed for higly demanding professionals working on specialist applications and intensive jobs. looking for maximum cutting speed and wear resistance in heavy cutting and drilling. They provide maximum cutting speed and wear resistance in heavy cutting. grinding and drilling.

**SILVER**
Husqvarna diamond tools at Silver level are developed for demanding professionals working on a variety of quick jobs during a workday in various all-round applications. They provide high cutting speed and wear resistance in all cutting. grinding and drilling.

**BRONZE**
Husqvarna diamond tools at Bronze level are developed for demanding professionals working occasionally with cutting an drilling jobs. looking for the best value between performance and price in all common cutting and drilling applications.

## DIAMOND BLADES WITH SMARTER FEATURES

To increase safety and performance when operating a handheld power cutter. Husqvarna now introduces new smarter features in the Elite-Cut. Vari-Cut and Tacti-Cut series. The smarter features give the operator a clear and immediate overview of the blade's wear. side clearance. direction of rotation and intended application.

## DIAMOND TOOLS FOR HANDHELD POWER CUTTERS

C **HUSQVARNA ELITE-CUT**
Gold level blades with Exo-Grit segments for smooth. efficient cut also in reinforced concrete. Diameters 300–400 mm in several versions optimised for the material to be cut. Providing 20% faster cut and 10% higher speed.
*According to internal field test compared to previous Elite-Cut series.

S **HUSQVARNA VARI-CUT**
Silver level blades with high cutting speed and a good balance between investment cost and cost per cut square metre. Diameters 300–400 mm in five versions depending on the application.

B **HUSQVARNA TACTI-CUT**
Bronze level blades optimised for less intensive professional cutting in most materials. Diameters 300–350 mm in five versions depending on the application.

## DIAMOND TOOLS FOR ANGLE GRINDERS

C **HUSQVARNA ELITE-CUT**
Gold level blades providing maximum cutting speed and life. Diameters 115–230 mm in five versions depending on the application.

C **HUSQVARNA ELITE-CUT S6 X-LOCK**
Gold level blades designed with continuous rim ideal when cutting on high precision materials such as tiles. X-lock design for safer and securer mount without tools.

C **HUSQVARNA ELITE-CUT S50 X-LOCK**
Gold level segmented blades ideal when cutting blocks or bricks. Speed bridge reduces lateral friction. better cooling and dust evacuation. X-lock design for safer and securer mount without tools.

S **HUSQVARNA VARI-CUT**
Silver level blades with high cutting speed and wear resistance in all materials. Diameters 115–230 mm in nine versions depending on the application.

B **HUSQVARNA TACTI-CUT**
Bronze level blades optimised for less intensive professional cutting in most materials. Diameters 115–230 mm in four versions depending on the application.

S **HUSQVARNA VARI-GRIND**
Silver level cup wheels for professional use. providing efficient grinding in all materials. Diameters 100–180 mm in four versions depending on the application.

B **HUSQVARNA TACTI-GRIND**
Bronze level cup wheels developed for less intensive use. offering good price performance. Diameters 115–180 mm in three versions depending on the application.

## SPECIAL APPLICATIONS

S **HUSQVARNA RESCUE BLADES**
Blades with brazed diamond technology. for all-round free cutting in materials as concrete. rubber brick. metal. steel etc. Suitable for rescue applications. Diameters 300–400 mm.

S **HUSQVARNA ABRASIVE DISCS**
Top-grade abrasive discs that can cut practically any material. such as stone. steel and railway rail. Diameters 300–400 mm.

C **HUSQVARNA ELITE-RING R 10**
Gold level ring saw blades designed for optimal cutting speed. even in the hardest and most reinforced concrete. Available in three hardness levels. Also available in Pre-Cut version with 6.0 mm wide segments. Diameter 370 and 430 mm.

S **HUSQVARNA VARI-RING R 20**
Silver level ring saw blades available in three hardness levels. Diameter 370 mm.

C **CUT-N-BREAK BLADE**
For the K 760 / K 3000 Cut-n-Break. Gold level blades with segment shape that produces excellent cutting characteristics and performance. Available in three hardness levels.

S **HUSQVARNA VARI-CHAIN**
A range of professional. premium and quality chains for sawing in reinforced concrete and other construction materials in different hardness.

C **HUSQVARNA ELITE-CHAIN**
Gold level diamond chains equipped with high-performing. wear-resistant sandwich segments providing long life in specific cutting applications.

C **HUSQVARNA ELITE-GUIDE BAR**
Guide bars developed to be the optimal choice of cutting equipment for any Husqvarna concrete chainsaw. Fits on both new and older models of Husqvarna concrete chainsaws.

## DIAMOND DRILL BITS

NEW G S **HUSQVARNA ELITE-DRILL TW AND VARI-DRILL TW SERIES**
A new range of thin-walled core drill bits specially designed for battery-powered and low-powered drill motors. Experience a faster and smoother drilling operation with quick and precise start. Available for both wet and dry drilling. Diameters 10–100 mm.

C **HUSQVARNA ELITE-DRILL SERIES**
Gold level drill bits delivering smooth. fast drilling in demanding applications. Available for various materials like heavily reinforced concrete. hard aggregate and abrasives. Diameters 92–350 mm.

S **HUSQVARNA VARI-DRILL**
Silver level drill bits with great performance and durability in heavy duty applications. Diameters from 18 – 300 mm in two versions depending on the application. 1 1/4" connector.

S **HUSQVARNA VARI-DRILL DRY**
Lightweight drill bits for dry indoor drilling by specialist professionals. Two versions available. Vacuum-brazed segments for drilling tiles and natural stone. Diameters 5–85 mm. Laser-welded segments for drilling concrete. bricks. and cement blocks. Diameters 37–200 mm.

B **HUSQVARNA TACTI-DRILL**
Bronze level drill bits with a good price/performance value for non intensive use in heavier applications. Diameters from 52–300 mm. 1 1/4" connector

## DIAMOND BLADES FOR MASONRY AND TILE SAWS

C **HUSQVARNA ELITE-CUT**
Gold level blades for fast. smooth cutting in most construction materials. at the lowest cutting cost per square metre. Diameters 300–1000 mm. in standard or silent version. depending on model and application.

## DIAMOND BLADES FOR WALL SAWS

C **HUSQVARNA W 1500**
Gold level blades for wall saws. designed to deliver where it matters. Provide reliable. smooth cutting with long blade life on a wide window of application. The W 1500 series also include Z-edge blades with increased sturdiness and life span. Diameters 600 –1500 mm.

S **HUSQVARNA W 1100**
Silver level blade for Husqvarna hydraulic and electric wall saws with an ideal design. Fits other machines as well. Diameters 600–1200 mm in three versions depending on the application.

## DIAMOND BLADES FOR HIGH- AND MID-POWERED FLOOR SAWS

C **HUSQVARNA F 1500 SERIES**
Gold level blades for floor saws. delivering superior performance. Available in versions optimised for efficient cutting in cured concrete. hard concrete. and asphalt. Diameters 500–1500 mm.

C **HUSQVARNA F 600**
Gold level blades for machines with motors of 25–50 kW. Diameters 300–1200 mm in four versions depending on the application.

C **HUSQVARNA L 600**
Gold level blades for slot cutting and traffic loops with sandwich design. Available in two versions with 6. 8 or 10 mm segment widths. Diameters 350–450 mm.

C **HUSQVARNA F 500**
Gold level blades with laser welded segments. optimised for Husqvarna FS 3500 G as well as electric floor saws. Diameters 500–800 mm.

## DIAMOND BLADES FOR LOW-POWERED FLOOR SAWS

S **HUSQVARNA ELITE-CUT**
Gold level blades with Exo-Grit segments for smooth. efficient cuts also in heavily reinforced concrete. Diameters 300–600 mm in several versions optimised for the material to be cut.

S **HUSQVARNA VARI-CUT**
Silver level blades with high cutting speed and wear resistance. Diameters 300–500 mm in three versions depending on the application.

B **HUSQVARNA TACTI-CUT**
Bronze level blades optimized for less intensive professional cutting in most materials. Diameters 300–400 mm in three versions depending on the application.

## DIAMOND BLADES FOR EARLY ENTRY SAWS

C **HUSQVARNA SOFF-CUT BLADES**
Patented gold level blades. supplied with skid plate. They are developed and tested for aggregate conditions. Soff-Cut blades are top quality and are designed specifically for the Soff-Cut system. Diameters 150–350 mm in three different series.

## DIAMOND WIRES

**ELITE-WIRE. VACUUM BRAZED RANGE**
Our wires for demanding applications. cutting pure steel or alloys and highly reinforced concrete. Delivers excellent performance/life balance.

**ELITE-